



## MS-GRO62SP (Single Point Stereo Speaker)

- > 6" Dual left and right dome tweeters
- > Kevlar woofer with butyl surround
- > 8 Ohms
- > Frequency Response: 45 Hz-20,000 Hz
- > Power Handling: 40 watts nom. 80 watts max.
- > Single point stereo speakers enable placement of a single unit in small areas
- > Grilles can be painted or covered to match or complement ceiling finish
- > White Frames can be painted to match or complement ceiling finish
- > 5 Year Limited Warranty
- > Overall dimensions: 8 3/8" round
- > Cut-out dimensions: 7 3/8" round x 2 7/8" deep
- > 91 dB Sensitivity



## MS-GRO82SP (Single Point Stereo Speaker)

- > 8" Dual left and right dome tweeters
- > Kevlar woofer with butyl surround
- > 8 Ohms
- > Frequency Response: 35 Hz-20,000 Hz
- > Power Handling: 50 watts nom. 100 watts max.
- > Single point stereo speakers enable placement of a single unit in small areas
- > Grilles can be painted or covered to match or complement ceiling finish
- > White Frames can be painted to match or complement ceiling finish
- > 5 Year Limited Warranty
- > Overall dimensions: 9 3/4" round
- > Cut-out dimensions: 8 5/8" round x 3 1/2" deep
- > 91 dB Sensitivity



## MS-BLCR52 (Single Point Stereo Speaker)

- > 5.25" Dual left and right dome tweeters
- > Kevlar woofers with butyl surround & phase plug pole pieces
- > Poly-switch overdrive protection
- > 1" pivoting textile soft dome tweeter
- > 8 Ohms
- > Frequency Response: 45 Hz-20 kHz
- > Power Handling: 50 watts nom, 100 watts max
- > Magnetically shielded
- > Compatible with 5.1, 6.1 & 7.1 home theater systems
- > LCR speaker-suitable for left, center, right applications
- > 12 dB/octave crossover
- > 91 dB sensitivity
- > 5 Year Limited Warranty
- > Overall dimensions: 9" x 15-3/4"
- > Cut-out dimensions: 7-7/8" x 14-7/16" x 3-1/2"D