Mustang Pro Audio Bundles

Commerical/Education Better Solution:

Wall Mount

PA-CEBWM - WALL MOUNT — **2 WALL MOUNT SPEAKERS, 1 POLE MOUNT AMPLIFER, 1 WIRELESS MICROPHONE**

Mustang — **Qty. 2**

EFG602B0D

- Foreground Speaker 6 1/2" 70V

- Built-in Transformers
- U-mount Brackets Included
- "Ferrofluid" Cooled Tweeters
- Injected ABS Cabinet

AKG — **Qty. 1**

WMS40PRO/55

- Wireless Lavalier Microphone

SR40 FLEXX- Diversity Reciever

- Audio Outputs: bal. XLR and unbal. 1/4" jack, output level adjustable, at rated deviation: 500 mV rms.
- Modulation: FM
- Audio Bandwidth: 35 to 20,000 Hz
- Signal/noise ratio: 120/230 V AC
- THD: typ. 0.8% (at rated 1 kHz)

PT 40 FLEXX- Microphone

- Modulation: FM
- Signal/Noise Ratio: typ. 110 dB (A)
- RF Output: typ. 10 mW (ERP)
- Battery Life: typ. 30 h (for 2200 mAh)
- Dimensions: 2.4 x 2.9 x 1.2 in.
- THD: typ. 0.8% (at 1 kHz)

Includes: Options CK 55 L: Clip-on

Microphone SR 40 Single: Diversity Reciever, SR 40 Dual: Diversity Reciever, PT 40 Pro: Microphone,HT 40 Pro: Microphone, CK 55 L: Clip-on Microphone

Atlas — **Qty. 1**

PA702

- Pole Mount Amplifer 2x 70 watts

- Recessed Screwdriver Adjustable Tone & Level Controls
- 30Hz – 20kHz Frequency Response
- 70 watts per channel (2) @ 8 ohms
- 30Hz – 20kHz Frequency Response
- Class AB Amplifier

The PA702 includes a unique (patent pending) mounting system that allows mounting-pole access through the amplifier via a sealed hole incorporated into the chassis design. Simply install the projector mounting pole, align the amplifier chassis hole with the 1.5" mounting tube, & clamp the unit at the desired height above the projector mount with the innovative pole clamp system included with the PA702. Afterwards, install the projector as normal. As a side benefit, the chassis "hole" mounting system provides the necessary security to prevent theft. Output is a strong 70 watts x 2 from the efficient rail tracking Class AB & switch mode power supply technology. Aside from the patent pending chassis design, the PA702, includes a host of other innovative features including an accessory outlet with AC current sense that allows the amplifier to respond instantly from stand-by mode when the projector is powered on. The slim profile chassis is also designed to work in a rack mount configuration. The optional rack mount kit allows single or dual mounting of the PA702 in the 1RU high configuration.