



Mustang Pro Audio Bundles

Commerical/Education Good Solution: Wall Mount




PA-CEGWM - WALL MOUNT

2 WALL MOUNT SPEAKERS, 1 POLE MOUNT AMPLIFIER, 1 WIRELESS MIC.



Mustang Qty. 2
EFG502B0D • Foreground Speaker
5" 70V

- Built-in Transformers
- U-mount Brackets Included
- "Ferrofluid" Cooled Tweeters
- Two -way Plastic Sealed Box
- Injected ABS Cabinet



Atlas Qty. 1
PA702 • Pole Mount Amplifier
2x 70 watts

- Recessed Screwdriver Adjustable Tone & Level Controls
- 30Hz – 20kHz Frequency Response
- 70 watts per channel (2) @ 8 ohms
- 30Hz – 20kHz Frequency Response
- Class AB Amplifier



AKG Qty. 1
WMS40PRO/55 • Wireless Lavalier
Microphone

- SR40 FLEXX- Diversity Reciever**
- Audio Outputs: bal. XLR and unbal. 1/4" jack, output level adjustable, at rated deviation: 500 mV rms.
 - Modulation: FM
 - Audio Bandwidth: 35 to 20,000 Hz
 - Signal/noise ratio: 120/230 V AC
 - THD: typ. 0.8% (at rated 1 kHz)
- PT 40 FLEXX- Microphone**
- Modulation: FM
 - Signal/Noise Ratio: typ. 110 dB (A)
 - RF Output: typ. 10 mW (ERP)
 - Battery Life: typ. 30 h (for 2200 mAh)
 - Dimensions: 2.4 x 2.9 x 1.2 in.
 - THD: typ. 0.8% (at 1 kHz)
 - Includes: Options CK 55 L: Clip-on

Microphone SR 40 Single: Diversity Reciever, SR 40 Dual: Diversity Reciever, PT 40 Pro: Microphone, HT 40 Pro: Microphone, CK 55 L: Clip-on Microphone

The PA702 includes a unique (patent pending) mounting system that allows mounting-pole access through the amplifier via a sealed hole incorporated into the chassis design. Simply install the projector mounting pole, align the amplifier chassis hole with the 1.5" mounting tube, & clamp the unit at the desired height above the projector mount with the innovative pole clamp system included with the PA702. Afterwards, install the projector as normal. As a side benefit, the chassis "hole" mounting system provides the necessary security to prevent theft. Output is a strong 70 watts x 2 from the efficient rail tracking Class AB & switch mode power supply technology. Aside from the patent pending chassis design, the PA702, includes a host of other innovative features including an accessory outlet with AC current sense that allows the amplifier to respond instantly from stand-by mode when the projector is powered on. The slim profile chassis is also designed to work in a rack mount configuration. The optional rack mount kit allows single or dual mounting of the PA702 in the 1RU high configuration.