MPTO-X85ULL Outdoor Wall Mount With Lock

Universal outdoor mount for 37-90" displays*

Best In Class Outdoor Wall Mount Solution

- Protected from rust, corrosion, and all types of weather with Dacromet® coating
- One touch lock & key system for extra security
- Universal design fits a wide range of displays
- Compatible with displays up to 200 lb and with VESA patterns up to 800 x 400mm
- Lateral shift & tilting capabilities
- Locking tilt angle with pretensioned tilt mechanism



* Display size is meant as a guide – Compatible display sizes can be larger or smaller depending on the VESA and weight of the display.

| SKU | Display Size* | Max VESA | Depth | Max Load |
|-------------|---------------|-----------|-------|-----------------|
| MPTO-X85ULL | 37-90" | 838x501mm | 2.2" | 200 lb |



DUAL KEYED LOCKS

Locking Brackets for High Security

Both hanger brackets come equipped with steel keyed locks to prevent theft and unwanted tampering



ADJUSTABLE TILT

Up to +15°/-5° Tilt

With more than 15° of forward tilt, can be positioned to a variety of angles

SLIM DESIGN

Less than 2.5" From Wall

Construction and design allows for displays to be held just 2.2" from the wall when mounted



MPTO-X85ULL Outdoor Wall Mount With Lock Outdoor mount for 37-90" displays



| Attribute V | alue | |
|---------------------------|--|--|
| Recommended display size* | 37" - 90" | |
| Lateral adjustment | Varies with display | |
| Weight capacity | 200lbs (91kg) | |
| Max mounting pattern | 838x501mm | |
| Min mounting pattern | 75x75mm | |
| Depth from wall | 2.2" (55.8mm) | |
| Tilt | +15°/-5° | |
| Construction | High-grade cold rolled steel | |
| Product Number | MPTO-X85ULL | |
| Mounting surface | Structural concrete, cinder block, wood, or metal stud | |
| Color | Black | |
| Indoor/Outoor | Outdoor | |
| Warranty | 5 year limitied | |

Universal tilting mount for outdoor displays 37" to 90" with dual security locks. Adjustable tilt wall mount with Universal hole pattern for outdoor displays. All components are Dacromet® coated and rated for outdoor use. Smooth tilt adjustments of 15° forward and 5° back with a locking knob and fixed tilt pin lock for a variety of viewing angles. Dual locks for security.

